

CENTURY PERISCOPE SERIES 2000 MARK II [®]

Designed to fulfill the demands of 35mm feature and commercial work, the Series 2000 Mark II T4 Periscope represents a remarkable advancement in the optical fidelity and usefulness of periscopic relay systems. For 35mm, 16mm & Video Camera work.



ADVANCED OPTICAL PERFORMANCE.

While ideal for shooting miniatures and tabletop setups, the Series 2000 Mark II T4 Periscope is equally at home in the real world – where lighting conditions are less easily controlled.

Displaying superior optical performance even at the widest aperture, the new Periscope captures unusual points of view in a wide range of shooting situations, both in studio and on location.

High Resolution.

The Series 2000 Mark II Periscope incorporates ultra-low dispersion Fluoro-Phosphate glass, dramatically reducing field curvature and chromatic aberration, which radically improves off-axis resolution.

Simplified Exposure Control.

Compatible with an extensive range of lenses, the S 2000 Mark II Periscope contains its own iris which reads directly in T-stops. The camera operator need only set the lens' aperture to 2.8, and the Periscope's iris to the T-stop the exposure calls for. The iris provides the control necessary to minimize vignetting. The Periscope's new internal focusing system makes it easy to utilize a standard follow focus unit.

Reaching Out.

The Series 2000 Mark II Periscope's 90° prism can be replaced with an optional Straight-view section*, extending the lens for impossible looking shoots in which the camera seems to dolly through a window or between the bars of a lion's cage.

Underwater Use.

Underwater Sleeve for underwater shoots available.

Features

- Super-sharp images – even wide open.
- Ultra-low dispersion Fluoro-Phosphate glass elements.
- Iris reads in T-stops.
- Works with standard follow focus.
- Offers both 90° & Straight View.
- Accepts a wide range of lenses. Geared iris & focus

Specifications	90° View	Straight View
T-Stop Range:	T4-T32	T4-T32
Camera Mounts:	Interchangeable	Interchangeable
Lens Mounts:	Interchangeable	Interchangeable
Dimensions:	20.71"L x 3.90"D x 3.10"W	21.72"L x 3.90"D x 3.10"W
Weight :	10 lbs. 3 oz.	10 lbs. 1 oz.

*IMAGES ARE INVERTED AND REVERTED